

Quality of Irrigation Water and Soil Amendment Effects on Leaching a Saline-Sodic Soil

JACK L. STROEHLEIN¹ AND BADIER J. ALAWI²

ABSTRACT

Field and laboratory experiments were conducted to determine the effects of three qualities of irrigation water and their interaction with gypsum ($\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$) or sulfuric acid (H_2SO_4) on infiltration rates and time and water requirement to leach a calcareous saline-sodic soil. In both field and laboratory experiments city water (lowest salt) reduced infiltration rates, while use of well water (highest salt) resulted in higher infiltration rates. Sulfuric acid improved the infiltration rates significantly with all sources of irrigation water. Gypsum improved infiltration rates only with well water. Equations were developed to predict time and amount of water required to leach soil columns to a given salt content for the three water qualities, and kind and rate of amendment applied.

The poorest quality irrigation water required the least time and amount of water to leach the soil, until the EC of the leachate was equal that of the irrigation water. Both (H_2SO_4 and $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$) reduced the time of leaching but required more water when compared with untreated columns.

INTRODUCTION

All irrigation waters carry dissolved salt (TDS—total dissolved salts) in solution. The kind and amount of salts vary from one source of water to another and from time to time. If irrigation agriculture is to remain productive, the salt residues derived from irrigation water must be carried beyond the root zone by leaching. Once soils are reclaimed, the leaching process must be rapid enough to be compatible with good plant yields. On the other hand, if excessive quantities of water are passed through the root zone, water is wasted, soluble nutrients are carried away and a serious drainage problem may develop. The time and amount of water required to accomplish a leaching operation depends to a large extent on the rate of water infiltration into the soil.

The soluble salt content (EC_e) and the exchangeable sodium percentage (ESP) of the soil affect infiltration rates and are generally in equilibrium with the salt and sodium in the irrigation water. Infiltration rates can be improved by using chemical amendments of high-salt water when reclaiming sodium-affected soils as shown by many investigators. Fireman and Bodman (3) obtained a high and constant permeability with a sodic soil when CaCl_2 was used in the percolating solution while, when distilled water was used, the permeability decreased drastically. Other studies (2,7) have shown that permeability increases with increasing electrolyte concentration of the percolating water even when the ESP is high.

¹Department of Soils, Water and Engineering, University of Arizona 85721, USA

²College of Agriculture and Forestry, Mosul, Iraq.

Sulfur and sulfur compounds have been used to improve infiltration (Eq. 4, 5, 11) and sulfuric acid has been shown to be an effective material on calcareous saline-sodic soils. Yahia, Miyamoto and Stroehlein (12) found evidence that sulfuric acid improved water penetration into some Arizona soils. Salt leaching experiments in Utah and California (8,9) have indicated that salt removal from soil follows a general pattern. In order to reduce the salt concentration of soil to about 20% of its original content, 1 cm of water is required for every 1 cm of soil considered. The permeability of sodic soils is a major barrier to successful reclamation. A solution to the problem was offered as mentioned previously by the use of high-salt water or the application of chemical amendments. This paper evaluates the effect of H_2SO_4 , gypsum, and water quality on soil infiltration rates and time and water requirement for leaching a calcareous saline-sodic soil.

MATERIALS AND METHODS

A field study was conducted on a Pima silty clay loam (Typic Torrifluent), saline-sodic phase (6), on the University of Arizona Safford Experiment Farm. Three sources of irrigation water of different qualities were used: well (EC = 3.2), river (EC = 1.6), and city (EC = 0.5) waters. Characteristics of the soils and the waters were given by Alawi, *et al.*, (1). The field experiment was a randomized split plot design with 9 main plots, and 27 subplots, including 3 replications. The main plots had been irrigated with the designated source of water for 3 years before the amendment application. Additional information on the field trial and soil analyses and sudangrass (*Sorghum sudanese*) yields for 1975 and 1976 have been published elsewhere (1). Infiltration rates were recorded in March 1975 before amendment application. One rate of gypsum (3.85 tonnes/ha.) and one rate of sulfuric acid (2.4 tonnes/ha.) were used in the field study. Irrigation of main plots continued with the designated source of water through the 1975 and 1976 growing seasons. Infiltration rates of each subplot were measured nine and fifteen months after amendment application.

A laboratory study of infiltration rates and leaching was conducted using soil columns. Soil was obtained from untreated subplots in the field and air dried, passed through a 2 mm sieve and 100 g were placed into soil columns, each being 30 cm in length and 2.5 cm in diameter. The outlet consisted of a rubber stopper through which a rigid plastic tube passed. A layer of glass wool was placed over the stopper to protect the drain from the overlying soil. The outlet tube drained into beakers. Each column was compacted until the bulk density of all were within the range of 1.23 to 1.28 g/cm³. Reagent grades of $CaSO_4 \cdot 2H_2O$ and 93% H_2SO_4 were added to the soil columns as follows: 3.85 or 19.35 tonnes/ha. $CaSO_4 \cdot 2H_2O$ and 2.24 or 11.25 tonnes/ha. H_2SO_4 . Each treatment was replicated three times. Gypsum was mixed with the upper 2 cm while H_2SO_4 was surface applied. Characteristics of soil columns are shown in Table 1. Columns were left overnight to let CO_2 escape and reduce its effect on infiltration rates. The same sources of irrigation water used in the field were added to the columns by a constant head device. Infiltration rates were recorded. Leachate from each pore volume was taken separately and the EC was measured. The leaching process continued until the EC of the leachate equalled that of the irrigation water.

$$Y = b_0 + b_1T + b_2T^2$$

Y = infiltration rate in cm/hour.

b_0 , b_1 , and b_2 = regression coefficients

T = time

Multiple regression was used to evaluate the collected leaching data.

Table 1 Infiltration rates from a field study using three water qualities and two chemical amendments, average of three replications.

Amendment	Well		River		City	
	ini. ^a	fin.	ini.	fin.	ini.	fin.
mm/hr						
Untreated	22.3	0.7	19.3	0.5	0.5	0.1
1975						
Gypsum	29.7	13.2	29.7	11.2	15.2	3.8
Sulfuric Acid	40.6	13.7	36.1	12.7	27.9	6.6
Control	23.9	9.1	19.1	6.4	3.3	1.3
1976						
Gypsum	39.4	13.7	33.0	11.7	21.6	5.1
Sulfuric Acid	48.3	17.5	41.1	15.0	33.0	9.1
Control	26.9	9.1	22.1	6.4	6.1	1.5

^aIni. refers to first reading, fin. refers to steady-state final reading taken eight hours after water application.

RESULTS AND DISCUSSION

The quality of irrigation water had a considerable effect on the infiltration rates in the field (Table 1). Water with the highest electrolyte concentration (well water) maintained good infiltration rates in spite of its high sodium content. Statistical analysis of the infiltration data indicated that city water (lowest salt content) reduced infiltration rates. Reduced infiltration was due to washing of salt from the soil surface and increasing the ESP.

Table 1 also shows the field infiltration rates of subplots treated with city, river and well waters, respectively, 9 and 15 months after amendment application. These data indicated that sulfuric acid increased the infiltration rates significantly over the controls with the three water treatments and, over gypsum, only with city water treatment. Gypsum increased the infiltration rates significantly only with well water, due to the effect of electrolyte concentration on the solubility of gypsum (1). Sulfuric acid increased infiltration rates due to its solubilizing effect on the relatively insoluble calcium compounds in the soil.

Comparison of infiltration rates of the subplots 15 months after amendment application indicated that there were considerably residual effects. Sulfuric acid treated subplots had the highest infiltration rates, control subplots the lowest. The 1976 measurements, however, were higher than those of 1975. This increase may have been due to seasonal effects or increased soil organic matter and improved soil structure resulting from the 1975 crop of sudangrass.

Table 2 shows the laboratory infiltration rates for the three waters. For each water the high rate of sulfuric acid had the highest infiltration rate followed by the low rate of sulfuric acid, the high rate of gypsum, the low rate of gypsum and then the control, respectively. Statistically, the high rate of sulfuric acid produced higher soil infiltration with all water qualities. No significant difference between the effect of the low rate of acid and the high rate of gypsum on the infiltration rates was found. The low rate of gypsum increased infiltration rates significantly above the control only with well water due to the electrolyte effect on the solubility of gypsum.

The quality of irrigation water controlled, to a certain extent, the time and amount of water required to leach the soil. Table 3 shows that, the poorer the quality irrigation water with respect to EC, the less time and water were required to leaching the

Table 2 Laboratory infiltration rates using three water qualities and two chemical amendments, average of three replications

Amendment	Rate	Well		River		City	
	T/ha.	ini. ^a	fin.	ini.	fin.	ini.	fin.
Gypsum	19.35	208.3	41.9	170.2	21.6	129.7	15.2
Gypsum	3.85	181.6	22.9	152.4	10.2	110.5	7.6
Sulfuric Acid	11.25	236.2	53.3	185.4	35.6	158.8	27.9
	2.24	182.9	27.9	165.1	15.2	138.7	12.7
Control		139.7	8.9	95.3	6.4	57.2	2.5

^aIni. refers to initial reading, fin. refers to final reading taken after steady-state infiltration had been reached.

untreated soil column until the EC of the leachate was equal to that of the irrigation water.

Table 3 shows the time and depth of water required to leach a column of Pima soil 30 cm deep until the EC of irrigation water equalled that of leachate. These data indicate that application of soil amendments had a positive effect on the reduction of the leaching time and an adverse effect on the required amount of water independent of water quality. The high rate of H_2SO_4 with well, river and city waters reduced the leaching time by 20, 21, and 26-fold compared to controls and used two-fold more water than the control. The increased water requirement when amendments were used would not be a problem in reclamation under field conditions since the EC of the soil is not reduced to the extent as in this study.

The other treatments influenced time and depth of water required depending on the type and rate of the chemical amendment. Table 4 shows that the change in the EC of the soil when the two rates of H_2SO_4 and the high high rate of $CaSO_4 \cdot 2H_2O$ were

Table 3 The depth of water and time required to leach Pima soil columns 30 cm deep until the EC of the leaching water equalled the EC of the leachate.

Source of water	Amendment rate	Time	Depth of water
	tonnes/ha.	days	cm
Well	Control	2.44	25.6
	Gypsum 19.35	2.17	45.8
	Gypsum 3.85	2.07	71.3
	H_2SO_4 11.25	0.68	30.6
	H_2SO_4 2.24	0.12	50.9
River	Control	4.23	30.5
	Gypsum 19.35	3.88	50.9
	Gypsum 3.85	3.39	81.5
	H_2SO_4 11.25	2.85	40.7
	H_2SO_4 2.24	1.44	56.0
City	Control	57.00	40.7
	Gypsum 19.35	8.88	71.3
	Gypsum 3.85	5.98	71.3
	H_2SO_4 11.25	2.42	45.8
	H_2SO_4 2.24	2.16	71.3

Table 4 Electrical conductivity (EC) of leachate vs time model to predict the time required to leach 30 cm of Pima soil to a specific EC with a given quality of water.

Treatment	Regression equations
Control	$EC = 1.942 + 0.245 (t/1,000) + 1.446 WQ - 0.511 (T/1,000) WQ$
2.24 T/ha. H_2SO_4	$EC = 5.192 - 2.717 (t/1,000) + 0.262 (t/1,000)^2$
11.25 T/ha. H_2SO_4	$EC = 8.316 - 7.228 (t/1,000) + 1.668 (t/1,000)^2$
3.85 T/ha. gypsum	$EC = 3.358 - 0.669 (t/1,000) + 0.031 (t/1,000)^2 + 0.736 WQ$
19.35 T/ha. gypsum	$EC = 1.569 - 0.395 (t/1,000) + 0.292 (t/1,000)^2$

T = Time in minutes

WQ = EC of irrigation water

EC = Desirable soil EC

Table 5 Electrical conductivity of leachate vs. depth of water model to predict the depth of irrigation water required to leach 30 cm of Pima soil to a specific EC.

Treatment	Regression equations
Control	$EC = 4.911 - 0.354D + 1.027WQ + 0.608D^2$
2.24 T/ha. H_2SO_4	$EC = 6.902 - 0.446D + 0.390D^2 + 1.046WQ$
11.25 T/ha. H_2SO_4	$EC = 7.399 - 0.302D + 0.317D^2 + 2.052WQ - 0.282WQD$
3.85 T/ha. gypsum	$EC = 4.576 - 0.167D + 0.161D^2 + 0.826WQ$
19.35 T/ha. gypsum	$EC = 4.545 - 0.151D + 0.235D^2 + 1.535WQ - 0.97DWQ$

D = Depth of water requirement in cm

WQ = $EC \times 10^3$ of irrigation water

EC = Desirable soil EC

used was dependent on time, but it was independent of water quality. The independence was considered to be related to the effects of sulfuric acid and the high rate of $CaSO_4 \cdot 2H_2O$ on the increased concentration of ions in the soil solution. At a low rate of gypsum, the change in soil EC_e was dependent on both time and water quality, but it did not depend on their interaction due to a low contribution of ions to the soil solution. The main source of ions for the control was from the irrigation water, which caused the change of the soil EC_e to be dependent on time, water quality, and their interaction.

Table 5 shows that only with high rates of sulfuric acid and gypsum the changes in the soil EC_e was a function of both amount and quality of water and their interaction due to the supply of ions from these two sources. The low rates of amendments and the control indicates that the change in EC_e of the soil was affected by depth and quality of water separately due to their low contribution to total ionic concentration.

CONCLUSIONS

This study showed that irrigation water quality controlled infiltration properties of a saline-sodic soil regardless of the effect of soil amendments. Sulfuric acid was more beneficial than gypsum when applied at equal S levels. Increasing the rate of amendments improved soil infiltration rates for the 3 irrigation waters studied. One equivalent of sulfuric acid had an effect similar to 5 equivalents of gypsum on the soil infiltration rate. With regard to leaching, it was found that the poorest quality of

irrigation water (highest salt) required the least time and amount of water to leach the soil column until the EC of the leachate equalled that of the irrigation water. The use of H_2SO_4 at high rates reduced the time required for leaching by 20, 21 and 26 times with well, river, and city water, respectively, but required almost two-fold more water than the controls. In general, more water was required to leach soil columns treated with gypsum than those treated with the H_2SO_4 and untreated soil. More water was required to leach soil columns treated with gypsum when well water was used for leaching than for river or city waters.

The change in the EC_e of the soil was found to be dependent on time only when 2 rates of H_2SO_4 and the high rate of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ were used as chemical amendments, but it was dependent on both time and quality of water and their interaction with the low rate of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ and control. Also, the change in the EC_e of the soil depended on both quality and amount of water and their interaction when high rates of H_2SO_4 and $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ were used, while it was affected by these 2 variables separately when low rates of H_2SO_4 and $\text{CaSO}_4 \cdot \text{H}_2\text{O}$ or when amendments were not used.

ACKNOWLEDGEMENT

A scholarship provided to the junior author by the Government of Iraq and financial assistance of the Arizona Mining Association are gratefully acknowledged.

LITERATURE CITED

1. Alawi, J., J. L. Stroehlein, E. A. Hanlon, Jr. and F. Turner, Jr. 1980. Quality of irrigation water and effects of sulfuric acid and gypsum on soil properties and sudangrass yields. *Soil Sci.* 129: 315-319.
2. Bodman, G. B. and C. Coleman. 1944. Infiltration of water into columns of stratified soil. *Soil Sci. Soc. Amer. Proc.* 8: 25-28.
3. Fireman, Milton and G. B. Bodman. 1939. The effect of saline irrigation water upon the permeability and base status of soils. *Soil Sci. Soc. Amer. Proc.* 4: 71-77.
4. Miyamoto, S. and J. L. Stroehlein. 1975. Sulfuric acid for improving water penetration into some Arizona soils. *Progressive Agric. in Arizona*, 27(2): 13-16.
5. Overstreet, R., J. C. Martin and H. M. King. 1951. Gypsum, sulfur and sulfuric acid for reclaiming an alkali soil of the Fresno series. *Hilgardia* 21: 113-127.
6. Post, D. F., D. M. Hendricks and J. M. Hart. 1977. Soils of the University of Arizona Experiment Station: Safford. *Univ. Ariz. Agric. Eng. and Soil Sci. Series* 77-1.
7. Quirk, J. P. and R. K. Schofield. 1955. The effect of electrolyte concentration on soil permeability. *J. Soil Sci.* 6: 263-178.
8. Reeve, R. C. 1948. Reclamation of alkali soil. *Utah Agr. Exp. Sta. Bull.* 346.
9. Reeve, R. C. and E. T. Doering. 1966. Use of high salt waters as a flocculant and source of divalent cations for reclaiming sodic soils. *Soil Sci.* 31: 138-161.
10. Tanji, K. K. 1969. Determination of solubility of gypsum in aqueous electrolyte as affected by ion concentration and ionic strength up to 0.15 M and at 20°C. *Envi. Sci.* 3: 6565-6661.
11. Tisdale, S. L. 1970. The use of sulphur compounds in irrigated aridland agriculture. *Sulphur Inst. J.* 9(1): 2-7.
12. Yahia, T. A., S. Miyamoto and J. L. Stroehlein. 1975. Effect of surface applied sulfuric acid on water penetration into dry calcareous and sodic soils. *Soil Sci. Soc. Amer. Proc.* 39: 1201-1204.

Instructions to Authors

The Libyan Journal of Agriculture is published annually by the Faculty of Agriculture, Al-Fateh University, Tripoli, (S.P.L.A.J.).

Contributions to the Libyan J. Agric. may be (i) papers of original research in any branches of agricultural science, pure and applied or (ii) Comments and letters to the Editor containing critical comments on previously published papers in the Libyan J. Agric. The research papers submitted for publication in the Libyan J. Agri. should not have been previously published or scheduled for publication in any other journal. It is preferable that the applied research papers be oriented toward solving agricultural problems in Libya.

Manuscripts: Papers must be in English. Papers should be typed in double-spacing on one side of the paper with sufficient margins (approximate size of the paper: 21.5 × 28 cm). Two copies of the manuscript should be submitted, the original typed copy along with a carbon copy.

Authors should organize their papers according to the following scheme as closely as possible: (1) Title of paper (2) Author's name (his affiliation written at the bottom of the first page); (3) Abstract (4) Introduction (5) Materials and Methods (6) Results and Discussion (7) Acknowledgement (8) Literature Cited (arranged alphabetically and by serial key numbers).

Citations in the text should be by key number in parentheses, with or without the author's name. The style of references should be as follows:

For Journal articles:

Gardner, W.R. 1956. Calculation of capillary conductivity from pressure plate outflow data. *Soil. Sci. Am. Proc.* 20: 317-320.

For Books:

Steel, R. D. and J. H. Torrie. 1960. *Principles and Procedures of Statistics*. McGraw-Hill Book Co., Inc., New York.

Tables should be numbered in the order of their appearance, and they should have brief titles. The structure should be self-explanatory with simple column headings giving all units. Each table should be typed on a separate sheet of paper.

Figures including both line-drawings and photographs, should be numbered consecutively in the order in which they are cited in the text. A list of titles of all figures must be supplied. Numbering of figures should be in soft pencil on the back of each figure. Photographs should be on glossy paper. Drawings should be made with china ink on suitable drawing paper. Line drawings should not be larger than 21 × 28 cm. The approximate position of tables and figures should be indicated in the manuscript.

Units should follow the metric system. Length is expressed in metres or centimetres. Mass is expressed in metric tons, kilograms, or grams. Yield or rate is expressed in metric tons/hectares or kg/hectares.

Authors should keep in mind that printer's proofs are intended for checking, not for alteration. All corrections should be made in the margin.

Authors are entitled to receive fifty reprints without covers, free of charge. Additional sets of fifty copies may be purchased at the following rate:

8 pages or less Libyan £2
12 pages or less Libyan £3

16 pages or less Libyan £4

24 pages or less Libyan £6

Editorial correspondence and manuscripts should be mailed to the Editor-in-Chief, The Libyan Journal of Agriculture, University of Al-Fateh, P.O. Box 2547, Tripoli, Libya.